

JOURNAL OF THE ARTIFICIAL INTELLIGENCE ENGINEERS CONSORTIUM

Volume: 02 Issue: 02 (2026)

<https://jaiec.org>

Memory-Dump Signatures for Automated Root-Cause Ranking in System Failures

Kai Moore¹, Sebastian M. Wilson²

^{1,2} Department of Electrical and Computer Engineering, Swanson School of
Engineering, University of Pittsburgh, Pittsburgh, Pennsylvania, USA

Abstract : *The increasing complexity of modern computing environments, encompassing distributed microservices, intricate operating system kernels, and heavily concurrent user-space applications, has severely exacerbated the difficulty of diagnosing system failures. When a catastrophic failure occurs, the system typically generates a memory dump, which serves as a forensic snapshot of the precise state of the machine at the moment of the crash. Traditionally, the analysis of these memory dumps has been a highly manual, labor-intensive process requiring profound domain expertise. To address this bottleneck, this paper proposes a novel framework for automated root-cause ranking utilizing advanced memory-dump signatures. By extracting complex multidimensional features from stack traces, heap metadata, and processor register states, the proposed methodology constructs a robust forensic signature for any given crash. These signatures are subsequently processed through a sophisticated ranking algorithm that evaluates historical fault data to predict and rank the most probable root causes. Through extensive evaluation on a comprehensive dataset of injected and naturally occurring software faults across both kernel and user-space domains, the automated ranking mechanism demonstrates a substantial improvement in diagnostic accuracy compared to traditional stack-hashing techniques. The results indicate that integrating memory-state anomalies with execution flow context significantly reduces the time to resolution for critical system failures, paving the way for more resilient and self-healing software infrastructures.*

Keywords : *memory dump analysis, automated debugging, root cause ranking, system reliability*

1. INTRODUCTION

1.1 The Challenge of System Failures

In the contemporary landscape of computing, the reliability and availability of software systems are of paramount importance. From cloud infrastructure and financial trading platforms to autonomous vehicular networks and healthcare life-support systems, uninterrupted operation is a critical requirement. However, despite rigorous software engineering practices, exhaustive testing protocols, and continuous integration pipelines, software defects inevitably escape into production environments. When these latent defects are triggered by specific, often highly improbable combinations of input data and execution states, they culminate in system failures or crashes. The immediate consequence of such a failure is an abrupt cessation of service, which can lead to significant data loss, degraded user experience, and substantial financial repercussions. To mitigate the impact of these outages, rapid diagnosis and remediation are essential. The diagnostic process traditionally begins

with an examination of the artifacts produced during the crash, the most vital of which is the memory dump or core dump. A memory dump represents a comprehensive, bit-for-bit snapshot of the volatile memory allocated to the faulting process, or in the case of a kernel panic, the entire physical memory of the machine. This artifact contains the execution context, including the processor registers, the call stack, dynamically allocated heap memory, and loaded shared libraries. Related work has addressed on the role of discount factor in offline reinforcement learning [1]. Despite the wealth of information contained within a memory dump, extracting actionable insights remains a formidable challenge. The sheer volume of data, often spanning gigabytes or even terabytes in enterprise environments, renders manual inspection practically impossible. Furthermore, the semantic gap between the binary representation of memory and the high-level source code constructs requires analysts to possess deep architectural knowledge and proficiency with complex debugging tools. Consequently, the resolution of critical system failures is frequently bottlenecked by the availability of highly skilled engineers who must painstakingly reconstruct the sequence of events leading to the crash. This reliance on human expertise not only prolongs system downtime but also introduces variability and human error into the root-cause analysis process. As systems continue to scale in both size and complexity, the traditional manual approach to memory dump analysis is rapidly becoming unsustainable, necessitating a paradigm shift towards intelligent, automated diagnostic methodologies. Sang examines adaptive quantization strategies for robust ML inference under distribution shift [2].

1.2 The Role of Automated Root-Cause Analysis

Automated root-cause analysis has emerged as a crucial area of research aimed at accelerating the resolution of software defects. The primary objective of automated root-cause analysis is to algorithmically identify the underlying bug or configuration error responsible for a given failure, minimizing the need for manual intervention. In the context of memory dump analysis, this involves parsing the raw binary data, reconstructing the execution context, and identifying anomalous states that correlate with known fault patterns. Early attempts at automating this process largely relied on simplistic heuristics and rule-based systems. For example, a common approach was to extract the call stack of the faulting thread and generate a cryptographic hash of the function names. This stack hash could then be compared against a database of known crashes to identify duplicate issues. While this method proved effective for basic bug triaging and deduplication, it is fundamentally limited in its diagnostic capabilities. Related work has addressed in context Semi-Supervised learning [3]. The primary limitation of stack hashing is its inability to capture the broader context of a failure. A crash may manifest in a deeply nested library function, such as a memory allocation routine, while the actual root cause resides in a completely different component that corrupted the heap metadata long before the crash occurred. In such scenarios, the stack trace merely reflects the symptom, not the disease. To overcome these limitations, modern automated root-cause analysis requires a more holistic approach that integrates information from multiple dimensions of the memory state. This includes analyzing the contents of the heap to detect memory corruption, examining the processor registers to identify invalid pointers or arithmetic anomalies, and correlating these findings with the execution flow represented by the stack trace. By synthesizing these disparate pieces of information into a unified memory-dump signature, it becomes possible to capture the unique forensic footprint of a specific root cause. The literature also considers modality asymmetries and circuit dynamics in modern transformers [4].

1.3 Contributions of This Research

This paper introduces a comprehensive framework for the automated generation and ranking of root causes based on multidimensional memory-dump signatures. The core premise of this research is that a sophisticated representation of the crash state, encompassing not only the execution path but also the underlying data structures, provides a significantly more accurate basis for fault diagnosis. The proposed methodology begins with the structural parsing of raw memory dumps, utilizing advanced unwinding techniques to reconstruct the call stack even in the presence of memory corruption or missing debug symbols. Subsequently, the framework extracts an extensive set of features from the stack, heap, and registers, encoding them into a highly structured signature vector. For a broader comparison, related research addresses evidence from a 52-country panel analysis [5]. The most significant contribution of this work lies in the development of an automated ranking mechanism that evaluates these signatures against a repository of historical fault data. Instead of merely identifying exact matches, the ranking algorithm employs advanced similarity metrics and probabilistic models to calculate the likelihood of various potential root causes. This approach is particularly valuable in environments where novel failures occur, as it can highlight structural similarities to previously resolved issues, thereby guiding developers toward the most promising avenues of investigation. Through rigorous empirical evaluation across diverse fault categories, including memory safety violations, concurrency issues, and logical errors, this paper demonstrates that the proposed signature-based ranking methodology significantly outperforms traditional diagnostic techniques. The findings presented herein contribute to the broader effort to build more resilient computing infrastructure by significantly reducing the mean time to resolution for critical software failures. Related work has addressed adaptive range guided multi-view depth estimation with normal ranking loss [6].

2. Background and Literature Review

2.1 Evolution of System Failure Diagnosis

The discipline of system failure diagnosis has undergone a significant evolution over the past several decades, driven by the escalating complexity of software architectures and the increasing demand for high availability. Dapper provides distributed request tracing, a complementary evidence source when a failure spans several services rather than a single process image [7]. In the early days of computing, diagnostic efforts were largely manual and ad hoc. Developers relied heavily on localized debugging techniques, such as inserting print statements into the source code or meticulously stepping through the execution flow using a debugger attached to a live process. These techniques, while effective for isolating straightforward logical errors in monolithic applications, rapidly became inadequate as systems grew more sophisticated. The advent of concurrent programming, distributed computing, and complex operating system kernels introduced entirely new classes of software defects, such as race conditions, deadlocks, and use-after-free vulnerabilities. These defects are notoriously difficult to reproduce in a controlled environment, rendering live debugging approaches highly ineffective. Another relevant line of investigation concerns brain-inspired computing accelerated by memristor technology [8]. To address the challenge of non-deterministic and transient failures, the industry shifted toward post-mortem analysis. When a critical failure occurs, the operating system intervenes and generates a core dump, preserving the exact state of the faulting process at the moment of termination. The analysis of these core dumps became a

specialized discipline, requiring proficiency with powerful debugging frameworks. Analysts would examine the call stack to identify the faulting instruction, inspect the contents of registers and memory addresses, and traverse complex data structures to reconstruct the chain of events. Despite the availability of post-mortem artifacts, the diagnostic process remained heavily dependent on human intuition and experience. The analyst had to manually synthesize disparate pieces of information, formulate hypotheses about the root cause, and verify these hypotheses against the source code. This iterative and time-consuming process highlighted the pressing need for automated tools capable of accelerating the forensic analysis of system crashes. The literature also considers stochastic failure analysis of reinforced thermoplastic pipes under axial loading and internal pressure [9].

2.2 Memory Dump Analysis Techniques

The development of automated memory dump analysis techniques has been a vibrant area of research, with numerous approaches proposed to extract meaningful patterns from raw binary data. Sentence-BERT provides a sentence-embedding approach for comparing the semantic content of textual records [10]. One of the foundational concepts in this domain is crash bucketing or deduplication. Large-scale software vendors and cloud service providers receive thousands of crash reports daily from their user base. To manage this massive influx of data, automated systems are employed to group similar crashes together into buckets. The underlying assumption is that crashes belonging to the same bucket share a common root cause and can therefore be resolved with a single patch. The most prevalent technique for crash bucketing is based on stack trace similarity. By extracting the sequence of function calls leading up to the crash and computing a hash of this sequence, crashes with identical or highly similar execution paths can be clustered together. Another relevant line of investigation concerns AI-Augmented automated triage for system error reporting using log and memory dump analysis [11]. While stack trace hashing has proven invaluable for managing the volume of crash reports, researchers have consistently pointed out its limitations in pinpointing the actual root cause. A significant body of literature has documented the phenomenon of symptom distance, wherein the point of failure observed in the stack trace is temporally and spatially distant from the original defect. For instance, a buffer overflow may corrupt adjacent memory regions without immediately triggering a crash. The system may continue to execute normally until a completely unrelated component attempts to access the corrupted data, resulting in a segmentation fault. In such cases, the stack trace points to the innocent component, actively misleading the debugging effort. To address this limitation, researchers have explored more advanced memory analysis techniques. Heap analysis tools attempt to reconstruct the state of dynamic memory allocation, identifying anomalies such as corrupted chunk headers, memory leaks, and overlapping allocations. Similarly, data-flow tracking techniques seek to trace the propagation of tainted or invalid data through the system registers and memory space. While these advanced techniques provide a deeper understanding of the crash state, they are often computationally expensive and difficult to integrate into a unified, automated diagnostic pipeline. Xiaoteng Ma examines offline reinforcement learning with value-based episodic memory [12]. Counterfactual audit and repair for multi-signal LiDAR segmentation [13] suggests a diagnostic robustness check: perturb one evidence component and inspect whether the proposed root cause changes for an intelligible reason.

2.3 Limitations of Current Automated Approaches

Despite the advancements in memory dump analysis, existing automated root-cause

diagnosis systems exhibit several critical limitations that hinder their effectiveness in production environments. First, many proposed solutions focus narrowly on specific classes of defects, such as memory corruption vulnerabilities or concurrency bugs. While these targeted approaches can be highly effective within their intended scope, they lack the generality required to handle the diverse array of failures encountered in real-world systems. A comprehensive diagnostic framework must be capable of identifying and ranking root causes across a wide spectrum of fault categories, from subtle logical errors to complex hardware-software interactions. Second, numerous existing techniques rely heavily on the availability of precise debugging information, such as symbol tables and source code mappings. In many commercial and production environments, binaries are heavily optimized and stripped of debug symbols to reduce their footprint and protect intellectual property. Consequently, automated analysis tools that depend on rich symbol information often fail when applied to real-world crash dumps. The literature also considers learning to substitute words with model-based score ranking [14]. Uncertainty-guided cross-head co-training in semantic segmentation [15] offers a related approach to learning with limited labels, but transferring it to failure signatures would require independently verified fault labels. Furthermore, a significant limitation of current approaches is the lack of a robust, holistic representation of the crash state. Most systems treat different aspects of the memory dump in isolation. For example, an automated tool might analyze the stack trace independently of the heap state, or focus solely on register anomalies without considering the broader execution context. This fragmented approach fails to capture the complex interdependencies that characterize many system failures. A subtle defect might only be identifiable by correlating a specific sequence of function calls on the stack with a particular pattern of memory allocation on the heap and a specific register value at the time of the crash. The absence of a unified framework capable of synthesizing these multidimensional features into a cohesive signature represents a major barrier to the advancement of automated root-cause ranking. The research presented in this paper specifically addresses these limitations by introducing a novel signature generation methodology that intrinsically links execution flow with memory state, providing a robust foundation for automated diagnosis even in the absence of complete debug information. An explanation of a high ranking is insufficient if it cannot identify the underlying evidence. The claims-audit framework [16] illustrates evidence-linked triage; memory-dump analysis can apply that principle by preserving the signature locations that influenced each candidate cause. The uncertainty-aware cross-modal fusion studied in CRUISE [17] provides a methodological comparison for combining heterogeneous evidence without assuming that every channel is equally informative.

3. Methodology for Signature Extraction and Ranking

3.1 Structural Parsing of Core Dumps

The foundational step in the proposed methodology involves the systematic and structural parsing of the raw memory dump. A core dump is fundamentally an unstructured binary file containing the memory segments of the process at the time of the crash, alongside metadata provided by the operating system kernel. The first objective is to impose structure upon this raw data, transforming it into an intermediate representation suitable for automated feature extraction. This process begins with the interpretation of the executable and linkable format headers embedded within the core file. These headers describe the layout of the virtual address space, identifying the start and end addresses of various memory segments, such as the executable text segment, the initialized data segment, the uninitialized data segment,

and the dynamic heap and stack regions. Accurately mapping these segments is critical, as it allows the analysis framework to distinguish between executable code, static variables, and dynamically allocated memory. For a broader comparison, related research addresses optimizing hybrid RIS-Aided ISAC systems in V2X networks: A deep reinforcement learning method for Anti-Eavesdropping techniques [18]. Once the memory landscape has been mapped, the next crucial step is stack unwinding. The call stack represents the historical sequence of function invocations that led to the current execution state. Unwinding the stack involves traversing the linked list of stack frames, utilizing information stored in the processor registers, specifically the stack pointer and the base pointer. For each frame, the framework identifies the return address, which corresponds to the instruction pointer in the calling function. In scenarios where binaries are compiled without frame pointers as an optimization strategy, the framework relies on specialized unwinding tables, such as the call frame information sections mandated by modern application binary interfaces. The stack unwinding process must be highly resilient, as the stack itself is frequently a victim of memory corruption during a crash. The proposed parsing module incorporates heuristic checks to detect corrupted stack frames and attempts to recover the execution flow by scanning the surrounding memory for valid return addresses. Concurrently, the parsing engine cross-references the identified memory addresses with available symbol tables, resolving raw memory addresses into human-readable function names and offset values, thereby bridging the semantic gap between the binary data and the structural architecture of the software. For a broader comparison, related research addresses adaptive weakly supervised Cross-Modal reliability learning for resource-constrained proxy-state recognition [19].




Figure 1: Architecture of the Automated Signature Extraction and Root

3.2 Signature Generation Framework

With the core dump structurally parsed and the execution context recovered, the methodology proceeds to the generation of the multidimensional memory-dump signature. The signature is conceptualized as a highly structured, fixed-length feature vector that encapsulates the forensic essence of the crash. The signature generation framework is divided into three primary feature extraction pipelines, each targeting a distinct aspect of the system state: stack features, heap features, and register features. The stack feature extraction pipeline focuses on the execution path. Instead of merely

recording the sequence of function names, this module extracts structural properties of the stack. This includes the depth of the call stack, which can indicate infinite recursion or stack exhaustion. It also captures the frequency and distribution of specific library calls, categorizing functions based on their domain, such as input-output operations, network communication, or memory management. Furthermore, the module calculates the relative offsets within the faulting function, providing fine-grained localization of the crash point. For a broader comparison, related research addresses neural modeling pipeline on multi-view human-object interactions [20]. The heap feature extraction pipeline is designed to identify anomalies within the dynamic memory allocator. The framework traverses the heap structures, parsing the metadata associated with allocated and free memory chunks. It extracts statistical features, such as the total volume of allocated memory, the fragmentation ratio, and the distribution of chunk sizes. More importantly, the module performs rigorous integrity checks on the heap metadata, detecting common corruption patterns such as overwritten boundary tags, corrupted free list pointers, and overlapping allocations. These structural anomalies are encoded as boolean flags or categorical variables within the signature vector. Finally, the register feature extraction pipeline analyzes the state of the processor registers at the exact moment of the crash. This involves examining the instruction pointer, stack pointer, and general-purpose registers for anomalous values. The framework checks for null pointers, misaligned memory addresses, and values that fall outside the mapped virtual address space. By synthesizing the structural data from the stack, the integrity metrics from the heap, and the anomaly indicators from the registers, the framework constructs a comprehensive and robust signature that provides a holistic representation of the failure state. The semantic-deviation paper models a document relative to historical structure [21]. A similar representation choice arises in dump signatures: a rare memory pattern should be compared with the correct software version before its rarity contributes to a root-cause score.

Table 1: Feature Categories Extracted for Memory-Dump Signatures

Feature Category	Description	Data Type	Extracted Attributes
Stack Execution	Sequential function calls and offsets	Categorical	Depth, Library Domains, Recursion Flags
Heap Integrity	Memory allocation metadata state	Numerical / Boolean	Fragmentation Ratio, Corruption Flags, Chunk Distribution
Register State	Processor register values at crash	Categorical	Null Pointers, Alignment Errors, Boundary Violations
Concurrency Context	Thread state and locking mechanisms	Boolean	Deadlock Indicators, Thread Count, Wait States

3.3 Automated Ranking Mechanism

The final component of the methodology is the automated ranking mechanism, which evaluates the generated memory-dump signature against a repository of historical fault data to predict and rank the most probable root causes. This process frames root-cause diagnosis as a specialized information retrieval and ranking problem. Given a newly generated query signature representing an unresolved crash, the objective is to retrieve the most relevant historical signatures and rank their associated root causes

based on their diagnostic likelihood. To achieve this, the framework employs an advanced similarity computation engine. Because the signature vector comprises a heterogeneous mix of categorical, numerical, and boolean features, a simple distance metric is insufficient. Deep learning from electronic health records offers a concrete heterogeneous-data application in which coding practices and observation frequency can affect the learned prediction [22]. Instead, the framework utilizes a composite similarity function. For numerical features, such as heap fragmentation ratios, continuous distance metrics are applied. For categorical features, particularly the sequence of function calls in the stack trace, the framework employs sequence alignment algorithms adapted from bioinformatics, which are capable of detecting similarities even when intermediate function calls differ due to varying execution paths or optimization levels. Related work has addressed multi-Objective perspective on robust ranking and selection [23]. The core of the ranking mechanism relies on a probabilistic ranking model trained on historical failure data. This model evaluates the composite similarity scores and assigns a probability value to each potential root cause. The model is designed to recognize that certain features possess higher diagnostic weight than others depending on the context. For instance, if the heap feature pipeline detects severe metadata corruption, the model automatically assigns higher relevance to historical root causes associated with buffer overflows or use-after-free vulnerabilities, even if the stack trace similarity is relatively low. Conversely, if the heap is pristine but the stack indicates a deep recursion within a specific module, the model prioritizes logical errors within that domain. The output of the ranking mechanism is an ordered list of potential root causes, presented to the analyst along with confidence scores and the specific features that contributed most heavily to the ranking decision. This explainable ranking approach not only accelerates the diagnostic process by pointing developers in the right direction but also builds trust in the automated system by providing transparent and interpretable reasoning for its predictions. Gao and colleagues examine advancing constrained ranking and selection with regression in partitioned domains [24]. Hyperdimensional multimodal uncertainty fusion [25] suggests retaining confidence for individual evidence channels before aggregating them into a root-cause score.

4. Experimental Evaluation and Results

4.1 Experimental Setup and Datasets

To rigorously evaluate the efficacy of the proposed memory-dump signature and automated ranking framework, a comprehensive experimental testbed was constructed. The primary objective of the evaluation was to determine the framework's ability to accurately rank the true root cause of a failure among a set of potential candidates, comparing its performance against traditional diagnostic baselines. The experimental setup involved a heterogeneous computing environment, utilizing virtualization to simulate diverse deployment scenarios. The operating systems included various distributions of Linux, representing the standard server environment, to capture a wide array of kernel configurations and user-space libraries. The evaluation dataset was meticulously curated to include both artificially injected faults and naturally occurring bugs extracted from real-world open-source projects. The dataset was stratified into three primary categories: memory safety violations, concurrency defects, and logical assertion failures. The literature also considers geometry-enhanced attentive multi-view stereo for challenging matching scenarios [26]. The fault injection process utilized a specialized framework designed to introduce precise mutations into the source code of target applications. These mutations included nullifying pointers, introducing off-by-one errors in array

iterations, removing synchronization primitives to induce race conditions, and forcing premature memory deallocations. The target applications were selected based on their widespread adoption and architectural complexity, including highly concurrent web servers, in-memory key-value stores, and relational database engines. Upon execution, the injected faults eventually triggered system crashes, resulting in the generation of core dumps. These core dumps were collected, cataloged, and paired with their known ground-truth root causes. To provide a robust baseline for comparison, the evaluation also implemented a traditional stack-hashing mechanism, which relies solely on the sequence of function names in the faulting thread's call stack to cluster and identify crashes. Fault labels in Lin's traffic application are inferred from structured temporal observations [27]. Root-cause ranking from memory signatures could adopt that evaluation logic by grouping related events before scoring a diagnosis, with separate tests for sequence leakage and unseen failure types.

Table 2: Composition of the Experimental Failure Dataset

Fault Category	Injected Faults	Natural Bugs	Total Memory Dumps
Memory Safety	150	45	195
Concurrency	85	30	115
Logical Errors	120	50	170
Total Dataset	355	125	480

4.2 Performance Evaluation

The performance of the automated ranking framework was evaluated using standard metrics from the field of information retrieval. The primary metrics employed were Top-1 Accuracy, Top-3 Accuracy, and Mean Reciprocal Rank. Top-1 Accuracy measures the percentage of cases where the true root cause was ranked as the absolute highest probability by the system. Top-3 Accuracy measures the percentage of cases where the true root cause appeared within the top three ranked suggestions, providing a measure of the system's utility in narrowing down the search space for developers. Mean Reciprocal Rank calculates the average of the reciprocal ranks of the correct root causes across all queries, offering a comprehensive assessment of the overall ranking quality. Li and colleagues examine asymptotic optimality of myopic ranking and selection procedures [28]. The experimental results demonstrated a significant performance advantage for the proposed multidimensional signature framework compared to the traditional stack-hashing baseline. Across the entire dataset, the signature-based approach achieved a highly competitive Top-1 Accuracy, indicating its robust ability to pinpoint the exact nature of the failure. The performance improvement was particularly pronounced in the category of memory safety violations. Traditional stack hashing frequently struggles with these types of defects due to the phenomenon of symptom distance, where the crash manifests during an innocuous operation entirely unrelated to the original memory corruption. Because the proposed framework incorporates heap integrity metrics and register anomaly detection into its signature, it successfully correlated the delayed crashes with their underlying memory corruption root causes, resulting in a dramatic increase in diagnostic precision. The disclosure study makes anomaly contributions inspectable [21]. Evaluation of dump ranking could likewise distinguish a correct top-ranked cause from an informative explanation, since a coincidental signature match may rank well while directing an engineer to the wrong evidence.




Figure 2: Comparative Performance Analysis of Root

Table 3: Root-Cause Ranking Accuracy Comparison

Diagnostic Method	Top-1 Accuracy	Top-3 Accuracy	Mean Rank	Reciprocal
Traditional Stack Hashing	42.5%	61.2%	0.54	
Basic Heap Analysis	38.1%	55.4%	0.49	
Multidimensional Signature	78.4%	92.1%	0.85	
Signature (Without Heap)	59.3%	76.8%	0.68	

4.3 Discussion of Results

The empirical results strongly validate the hypothesis that a holistic representation of the memory state is essential for automated root-cause ranking. The ablation study, which selectively disabled specific feature extraction pipelines, provided deep insights into the relative importance of different signature components. As shown in the performance tables, disabling the heap analysis module resulted in a severe degradation of accuracy, particularly for memory-related defects. This confirms that stack traces alone provide an incomplete and often misleading picture of the crash state. By incorporating structural heap metadata, the system gains the ability to detect latent corruption that silently undermines system stability before ultimately precipitating a crash. Related work has addressed frequency spectral prior guided graph learning for degradation decoupling in reliable battery SOH estimation [29].

Table 4: Ablation Study on Signature Feature Importance

Feature Configuration	Memory Accuracy	Safety	Concurrency Accuracy	Logical Error Accuracy
Full Signature Vector	81.2%		71.4%	85.3%
Stack Features Only	35.6%		68.2%	82.1%
Heap Features Only	65.8%		22.5%	15.4%
Register Features Only	41.2%		30.1%	28.7%

Furthermore, the results highlight the effectiveness of the probabilistic ranking model. In scenarios involving highly complex concurrency bugs, such as race conditions that manifest with slightly different stack traces upon each occurrence, the strict sequence matching of traditional methods failed entirely. The proposed framework, however, leverages sequence alignment algorithms and contextual features, allowing it to recognize the structural similarities between different manifestations of the same concurrency defect. Although Top-1 Accuracy for concurrency issues was lower than for logical errors, the Top-3 Accuracy remained remarkably high. This indicates that while the system may occasionally struggle to definitively isolate the single most probable root cause in highly non-deterministic scenarios, it consistently succeeds in bounding the problem, providing developers with a highly restricted and relevant set of hypotheses to investigate. The overall consequence is a profound reduction in manual diagnostic effort and a corresponding decrease in system downtime. Related work has addressed battery SOH prediction under different conditions via MBLSTM and iTransformer with anomaly detection and explainability [30].

5. Conclusion and Future Directions

5.1 Summary of Contributions

This paper has presented a comprehensive and highly effective methodology for the automated ranking of root causes in system failures through the use of multidimensional memory-dump signatures. Recognizing the severe limitations of traditional manual debugging and simplistic stack-hashing techniques, this research proposed a paradigm shift toward holistic memory state analysis. By systematically parsing core dumps to reconstruct the execution context and subsequently extracting a diverse array of structural, statistical, and integrity-based features from the stack, heap, and processor registers, the framework generates a robust forensic signature. This signature captures the complex interdependencies and subtle anomalies that characterize modern software defects. The literature also considers nonconvex and adaptive Multi-Label learning for highly incomplete labels [31]. The integration of these signatures with a probabilistic ranking algorithm represents a significant advancement in automated diagnostics. Rather than relying on exact matches, the system intelligently evaluates similarities across multiple dimensions, allowing it to accurately rank root causes even in the presence of symptom distance and non-deterministic execution paths. Extensive empirical evaluation on a diverse dataset of injected and natural faults demonstrated that the proposed framework substantially outperforms conventional methods, particularly in diagnosing complex memory safety violations. By providing developers with highly accurate and explainable root-cause rankings, this automated system directly addresses the critical bottleneck of human expertise in failure resolution, enabling faster recovery times and contributing to the overall resilience of complex computing infrastructures. For a broader comparison, related research addresses unified long video inpainting and outpainting via overlapping High-Order Co-Denoising [32].

5.2 Open Challenges and Future Work

While the proposed framework demonstrates significant diagnostic capabilities, several open challenges remain, paving the way for future research directions. One primary limitation is the substantial computational overhead and storage requirements associated with processing massive core dumps, particularly in enterprise environments where memory footprints can exceed hundreds of gigabytes. Future work must investigate optimized techniques for partial dump generation and selective feature extraction, aiming to capture the essential diagnostic information while minimizing resource consumption. Additionally, the increasing prevalence of

memory-safe languages and advanced hardware mitigation technologies, such as memory tagging extensions, will fundamentally alter the landscape of software failures. The signature generation framework must evolve to incorporate telemetry and context provided by these modern architectural features. Huang et al. retain human review after automated prioritization [16]. A practical extension of root-cause ranking would likewise record whether an engineer accepted, rejected or revised the proposed cause, allowing future evaluation to distinguish analyst utility from ranking accuracy alone. Furthermore, applying this methodology to highly distributed, microservice-based architectures presents a formidable challenge. In such environments, a failure in one service is often the cascading result of a subtle error in an entirely different distributed component. Future research should explore the correlation of memory-dump signatures across multiple interconnected nodes, integrating distributed tracing data to construct a global failure context. Object-centric industrial video anomaly detection [33] offers a prospective additional evidence stream for incident diagnosis, while visual anomalies and memory-dump signatures must retain separate provenance. Lastly, investigating the integration of advanced machine learning models, such as graph neural networks, to directly process the structural representation of the memory state, rather than relying on engineered feature vectors, represents a promising frontier for further improving the accuracy and generalization of automated root-cause analysis systems. The literature also considers numerical modeling and failure analysis of caisson foundations subjected to the monotonic lateral loads [34].

References

- Hu, H., Yang, Y., Zhao, Q., & Zhang, C. (2022, June). On the role of discount factor in offline reinforcement learning. In *International conference on machine learning* (pp. 9072-9098). PMLR.
- Sang, Y. (2026, March). Adaptive Quantization Strategies for Robust ML Inference Under Distribution Shift. In *Proceedings of the 2026 5th International Conference on Cyber Security, Artificial Intelligence and Digital Economy* (pp. 362-368).
- Fan, J., Rosu, P., Wang, A. T., Carin, L., & Cheng, X. (2026). In context semi-supervised learning. In *Proceedings of the International Conference on Learning Representations*. <https://openreview.net/forum?id=lqrpmqrTnH>
- Huang, Y., Roth, K., Bouniot, Q., Xu, W., & Akata, Z. (2026). Dissecting Multimodal In-Context Learning: Modality Asymmetries and Circuit Dynamics in modern Transformers. *arXiv preprint arXiv:2601.20796*.
- Jin, H., Tsai, F. S., & Martinez-Vazquez, J. (2025). Optimal expenditure decentralization for sustainable development: evidence from a 52-country panel analysis. *Financial Innovation*, 11(1), 111.
- Ding, Y., Li, Z., Huang, D., Zhang, K., Li, Z., & Feng, W. (2022, December). Adaptive range guided multi-view depth estimation with normal ranking loss. In *Asian Conference on Computer Vision* (pp. 280-295). Cham: Springer Nature Switzerland.
- Sigelman, B. H., Barroso, L. A., Burrows, M., Stephenson, P., Plakal, M., Beaver, D., et al. (2010). Dapper, a large-scale distributed systems tracing infrastructure. Technical Report, Google.
- Liu, Chenchen, Fuqiang Liu, and Hai Li. "Brain-inspired computing accelerated by memristor technology." In *Proceedings of the 4th ACM International Conference on Nanoscale Computing and Communication*, pp. 1-6. 2017.

- Wang, Y. Y., Lou, M., Wang, Y., Wu, W. G., & Yang, F. (2022). Stochastic failure analysis of reinforced thermoplastic pipes under axial loading and internal pressure. *China Ocean Engineering*, 36(4), 614-628.
- Reimers, N., & Gurevych, I. (2019). Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of EMNLP-IJCNLP*.
- Li, Y. (2026, June). AI-augmented automated triage for system error reporting using log and memory dump analysis. In *2026 7th International Conference on Big Data & Artificial Intelligence & Software Engineering (ICBASE)* (pp. 572-577). IEEE.
- Xiaoteng Ma, Yiqin Yang, Hao Hu, Qihan Liu, Jun Yang, Chongjie Zhang, Qianchuan Zhao, and Bin Liang. Offline reinforcement learning with value-based episodic memory. *arXiv preprint arXiv:2110.09796*, 2021b.
- Meng, X., & Lin, J. (2026). CARTN: Counterfactual Audit and Repair for Trust-Aware Multi-Signal Streaming LiDAR Segmentation. *Information Fusion*, 104809.
- Liu, H., & Henao, R. (2025, April). Learning to substitute words with model-based score ranking. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)* (pp. 11551-11565).
- Fan, J., Gao, B., Jin, H., & Jiang, L. (2022). UCC: Uncertainty guided cross-head co-training for semi-supervised semantic segmentation. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)* (pp. 9937–9946). IEEE. <https://doi.org/10.1109/CVPR52688.2022.00971>
- Huang, D., Song, L., Chen, Y., He, S., Wang, R., Shen, H., & Chu, W. (2026). AnExplainable AI Engineering Framework for Claims-Only First-Stage Provider Audit Triage Using SHAP-Guided Hybrid Retrieval-Augmented Generation. *Machine Learning and Knowledge Extraction*, 8(9), 279.
- Wang, J., Xu, Y., Li, Y., Khargonekar, P., & Faruque, M. A. A. (2026). CRUISE: Vision-Language Model-Guided Uncertainty-Aware Cross-Modal Sensor Fusion for Robust Autonomous Driving. *arXiv preprint arXiv:2608.09202*.
- Yao, Y., Zhu, Z., Miao, P., Cheng, X., Shu, F., & Wang, J. (2025). Optimizing hybrid RIS-aided ISAC systems in V2X networks: A deep reinforcement learning method for anti-eavesdropping techniques. *IEEE Transactions on Vehicular Technology*, 74 (6), 9224-9239.
- Meng, X., & Lin, J. (2026). AWCRL: Adaptive Weakly Supervised Cross-Modal Reliability Learning for resource-constrained proxy-state recognition. *Pattern Recognition*, 114998.
- Zhang, J., Luo, H., Yang, H., Xu, X., Wu, Q., Shi, Y., ... & Wang, J. (2023). Neuraldome: A neural modeling pipeline on multi-view human-object interactions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (pp. 8834-8845).
- Sun, F., He, S., Wang, R., Ke, L., Shen, H., & Liao, Q. (2026). Modeling Structural Deviation in 10-K Risk Factors: A Semantic Anomaly Detection and Explainable AI Approach. *Risks*, 14(4), 87.
- Rajkomar, A., Oren, E., Chen, K., Dai, A. M., Hajaj, N., Hardt, M., et al. (2018). Scalable and accurate deep learning with electronic health records. *NPJ Digital Medicine*, 1, 18.

- Liu, W., Gao, S., & Lee, L. H. (2017, December). A multi-objective perspective on robust ranking and selection. In 2017 Winter Simulation Conference (WSC) (pp. 2116-2127). IEEE.
- Gao, F., Gao, S., Xiao, H., & Shi, Z. (2018). Advancing constrained ranking and selection with regression in partitioned domains. *IEEE Transactions on Automation Science and Engineering*, 16(1), 382-391.
- Chen, L., Wang, J., Mortlock, T., Khargonekar, P., & Al Faruque, M. A. (2025, June). Hyperdimensional uncertainty quantification for multimodal uncertainty fusion in autonomous vehicles perception. In 2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (pp. 22306-22316). IEEE.
- Liu, Y., Cai, Q., Wang, C., Yang, J., Fan, H., Dong, J., & Chen, S. (2024). Geometry-enhanced attentive multi-view stereo for challenging matching scenarios. *IEEE Transactions on Circuits and Systems for Video Technology*, 34(8), 7401-7416.
- Lin, Y. (2024). Design of urban road fault detection system based on artificial neural network and deep learning. *Frontiers in neuroscience*, 18, 1369832.
- Li, Y., Gao, S., & Shi, T. Z. (2023). Asymptotic optimality of myopic ranking and selection procedures. *Automatica*, 151, 110896.
- Guo, F., Tao, S., Zhang, J., Zhou, H., Ji, J. J., Dong, D., & Mo, H. (2026). Frequency Spectral Prior Guided Graph Learning for Degradation Decoupling in Reliable Battery SOH Estimation. *Green Energy and Intelligent Transportation*, 100446.
- Guo, F., Xu, K., Zhang, Z., Zhou, H., Chen, G., Hu, J., ... & Mo, H. (2025). Battery SOH prediction under different conditions via MBLSTM and iTransformer with anomaly detection and explainability. *IEEE Open Journal of the Computer Society*.
- Luo, T., Li, Q., Jiang, M., & Hou, C. (2025). Nonconvex and Adaptive Multi-Label Learning for Highly Incomplete Labels. *Knowledge-Based Systems*, 114784.
- Lyu, S., Mao, S., & Ma, Y. (2025). Unified Long Video Inpainting and Outpainting via Overlapping High-Order Co-Denoising. *arXiv preprint arXiv:2511.03272*.
- Yuan, M., Long, Q., Wu, Q., Li, Z., Zhao, Y., Wang, L., ... & Xu, M. (2026, September). O-VAD: Industrial Video Anomaly Detection Through Object-Centric Tracking and Reasoning. In *European Conference on Computer Vision* (pp. 285-302). Cham: Springer Nature Switzerland.
- Malik, B. A., Mandhaniya, P., Soni, A. K., & Ouyang, Z. (2024). Numerical modeling and failure analysis of caisson foundations subjected to the monotonic lateral loads. *Ocean Engineering*, 309, 118491.